



L4A-HMDM-8-P-SGW

LDF4-50A SureFlex™ Jumper with interface types 4.3-10 Male and 7-16 DIN Male with HELIAX® SureGuard weatherproofing, 8 ft

- **WARNING: DO NOT MATE WITH 4.1-9.5 DIN**

General Specifications

| | |
|------------------------------------|--------------------|
| Body Style, Connector A | Straight |
| Body Style, Connector B | Straight |
| Cable Family | LDF4-50A |
| Interface, Connector A | 4.3-10 Male |
| Interface, Connector B | 7-16 DIN Male |
| Nominal Size | 1/2 in |
| Length | 2.438 m 8.000 ft |
| Specification Sheet Revision Level | A |

Electrical Specifications

| | |
|----------------------------------|---|
| 3rd Order IMD Static | -159.00 dBc (relative to carrier) -116.00 dBm |
| 3rd Order IMD Static Test Method | Two +43 dBm carriers |
| DTF, Connector A | -34.00 dB |
| DTF, Connector B | -34.00 dB |

Jumper Assembly Sample Label

Batch 0123456789 | **Manufacturing Date** (two digit year and week) US22 1240 | **Product Revision** /A
Manufacturing Plant US22 | **Product Revision** /A
Part Number F4A-DMDM-2M-P
 2 M (6.562 FT)
 SUREFLEX ASSEMBLY
 U.S. PATENT 5802710
 Product of UNITED STATES
Serial Number 12US220001242

L4A:HMDM-8P-SGW

POWERED BY



Return Loss/VSWR

| Frequency Band | VSWR | Return Loss (dB) |
|----------------|------|------------------|
| 698–960 MHz | 1.07 | 30.00 |
| 1700–2200 MHz | 1.07 | 30.00 |
| 2200–3000 MHz | 1.08 | 28.00 |

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU
China RoHS SJ/T 11364-2006
ISO 9001:2008

Classification

Compliant by Exemption
Above Maximum Concentration Value (MCV)
Designed, manufactured and/or distributed under this quality management system



Included Products

LDF4-50A — LDF4-50A, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/2 in, black PE jacket