

NOT for Patient-Care Vicinity – UL 1363 1U Rackmount Power Strip with 12 Hospital-Grade Outlets, 15 ft. Cord

MODEL NUMBER: RS1215-HG



Medical-grade rackmount power strip with long 15 ft. cord provides power distribution outside of patient-care vicinities.

Description

The RS1215-HG Medical-Grade Rackmount Power Strip supplies power outside of patient-care vicinities, such as administrative areas, rack enclosures or network closets. In a rack, it occupies just 1U of space. Compliant with UL 1363 specifications, this 120V, 50/60 Hz power strip features a NEMA 5-15P-HG hospital-grade plug and 12 NEMA 5-15R-HG hospital-grade outlets.

Six of the outlets are oriented at the front of this power strip and six are oriented at the rear, so your power is located conveniently where you need it.

A built-in resettable 15A circuit breaker controls power to all outlets and protects the power strip against overloads. The lighted power switch confirms power on/off status at a glance, and has a locking safety cover to prevent accidental shut-off. The 15 ft. cord provides ample reach to a power source.

Detachable mounting ears can be reoriented so you can put this power strip in a variety of installations: in a rack, on a wall or under a counter or table. The all-metal housing ensures safety and is guaranteed to last a long time in demanding surroundings.

Features

Versatile Power Distribution Outside of Patient-Care Vicinities

- Ideal for use in rackmount, wallmount and under-counter installation in administrative areas and other areas outside of patient-care vicinities
- Unfiltered electrical pass-through makes this strip ideal for distributing alternate waveform UPS or generator power in rack enclosures and network closets

Highlights

- Occupies 1U of space in a standard 19-in. rack
- Approved for use outside of patient-care vicinities
- Complies with UL 1363 specifications
- 15 ft. cord with NEMA 5-15P-HG hospital-grade plug
- 12 NEMA 5-15R-HG hospital-grade outlets

Package Includes

- RS1215-HG UL 1363 Medical-Grade Rackmount Power Strip with 12 15A Hospital-Grade Outlets and 15 ft. Cord
- Owner's Manual



- 120V, 50/60 Hz power strip complies with UL 1363 specifications

Versatile Medical-Grade Solution

- 12 NEMA 5-15R-HG hospital-grade outlets provide consistent power
- 6 outlets are on front of unit, 6 are on rear of unit
- Rugged, all-metal housing for long life in demanding environments

Premium Safety Features

- Resettable 15A circuit breaker protects against dangerous overloads
- Illuminated on/off switch has locking safety cover to prevent accidental shut-off

Ready to Use Right Out of the Box

- Detachable mounting flanges are configurable for versatile mounting orientation in a rack, on a wall or under a counter

Specifications

| OVERVIEW | |
|------------------------------------|---------------------|
| UPC Code | 037332099365 |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 15A 120V |
| Input Plug Features | Hospital Grade Plug |
| Voltage Compatibility (VAC) | 120 |
| Input Plug Type | NEMA 5-15P-HG |
| Input Cord Length (ft.) | 15 |
| Input Cord Length (m) | 4.57 |
| Integrated Cord Clip | No |
| OUTPUT | |
| Frequency Compatibility | 50 / 60 Hz |
| Output (Watts) | 1800 |
| Output Receptacles | (12) 5-15R-HG |
| Circuit Breaker (amps) | 15 |
| Transformer Accommodation | (5) Yes |
| Outlet Orientation | 6 front / 6 rear |



| | |
|----------------------------------------------|-----------------------------------------------------------------------------------|
| Right-Angle Outlets | No |
| USER INTERFACE, ALERTS & CONTROLS | |
| Switches | Red illuminated 2 position switch controls power to all outlets |
| Locking Switch Cover | Transparent locking switch cover prevents accidental shutoff |
| PHYSICAL | |
| Antimicrobial Coating | No |
| Color | Black |
| Color (AC Line Cord) | Black |
| Form Factors Supported | 1U rackmount, wallmount and undercounter installation supported |
| Included Mounting Accessories | Rackmount flanges |
| Integrated Keyhole Mounting Slots | No |
| Material of Construction | Metal |
| Outlets Measurement (Center to Center) | Distance between Front outlets = 83.35mm; Distance between Rear outlets = 165.1mm |
| Receptacle Color | White |
| Shipping Dimensions (hwd / cm) | 23.88 x 5.72 x 51.56 |
| Shipping Dimensions (hwd / in.) | 9.40 x 2.25 x 20.30 |
| Shipping Weight (kg) | 2.77 |
| Shipping Weight (lbs.) | 6.10 |
| Unit Dimensions (hwd / cm) | 4.4 x 43.9 x 10.2 |
| Unit Dimensions (hwd / in.) | 1.75 x 17.3 x 4 |
| Unit Weight (kg) | 2.09 |
| Unit Weight (lbs.) | 4.6 |
| SPECIAL FEATURES | |
| TVSS Grounding | Back panel nut and bolt grounding lug |
| Built-in Cable Management | No |
| STANDARDS & COMPLIANCE | |
| Canada | cUL (Series Number: AGIP120V6IPRM) |
| UL1363 (Power Tap) | UL1363 (UR status) (Series Number: AGIP120V6IPRM) |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>