

# Multiband Slim Omni Antenna 1x Cellular (600-7125MHz), SMA



- ❖ One ultra-wideband (617-7125MHz) to support 4G/5G as well as Wi-Fi 6E
- ❖ Ground plane independent
- ❖ Includes sealing gasket at bottom for fleet mounting
- ❖ Indoor and Outdoor rated IP66 design with UV stabilized cover
- ❖ Ideal for Fixed and Mobile installations in Industrial IoT, Automations, Smart City, EV-Chargers, Smart Metering, Public Safety and such

Connector Option	Product SKU	Ventev Part #
SMA Male	605245	VL-UE10-SSM

For more information or to purchase, contact Ventev: 800.851.4965 or [sales@ventev.com](mailto:sales@ventev.com)

Electrical Specifications – Cable 1 (4G/5G Elements, labeled LTE)					
Frequency Bands, MHz	617-698	698-960	1710-2700	3300-4200	4900-7125
Polarization	Linear Vertical				
Azimuth (HBW)	Omni (360°)				
VSWR	≤2.2	≤2.0	≤2.0	≤1.8	≤2.0
Peak Gain, dBi	2.5	4.0	6.0	6.0	4.5
Max Input Power per Port, watts	20				
Impedance, ohm	50				
Mechanical Specifications					
Product Dims	Ø145mm x 40mm (Ø5.7in x 1.6in)				
Connector/Lead	1x SMA Male, RG316, 10ft Lead				
Radome Material/ Color	UV Stabilized ABS Black				
Operating Temperature	-40 to +85 °C (-40 to 185 °F)				
Ingress Protection	IP66				
Mounting	Stud Mount Through 0.8" hole; Max. Panel Thickness ¼" (Sealing pad on the back for sealing and minimize shaking)				
Application	Indoor or Outdoor				
Product Weight	0.4 lbs				