

Product data sheet

Specifications



Rack PDU, Metered, 1U, 20A, 120V, (8) 5-20



AP7801B

Product availability : Stock - Normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

Main Input Voltage	100 V 120 V
PDU Type	Metered
Main Output Voltage	120 V
Input Connection Type	NEMA L5-20P
Number of rack unit	1U
Cable length	12 ft (3.66 m)
Number of cables	1
Provided Equipment	Cord retention bracket(s) Installation guide Rack Mounting brackets User Manual

Physical

Height	1.73 in (4.4 cm)
Width	17.48 in (44.4 cm)
Depth	4.02 in (10.2 cm)
Net Weight	3.81 lb(US) (1.73 kg)
Mounting Location	Front Rear
Mounting preference	No preference
Mounting Mode	Rack-mounted
Mounting position	Horizontal

Input

Line Rated Current	16 A
Input current limits	20 A
Load Capacity	1920 VA
Input Frequency	50/60 Hz

Output

Number of power socket outlets 8 NEMA 5-20R

Conformance

Product Certifications cUL Listed
CSA
UL Listed

Standards FCC Part 15 class A
ICES-003
UL 60950

Environmental

Ambient Air Temperature for Operation 23...113 °F (-5...45 °C)

Relative Humidity 5...95 %

Operating altitude 0...10000 ft

Ambient Air Temperature for Storage -13...149 °F (-25...65 °C)

Storage Relative Humidity 5...95 %

Storage altitude 0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

Category 80230-IG SEBA TO SEUSA

Discount Schedule BMS1

GTIN 731304331469

Returnability No

Country of origin PH

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 2.52 in (6.4 cm)

Package 1 Width 13.27 in (33.7 cm)

Package 1 Length 18.50 in (47 cm)

Package 1 Weight 6.42 lb(US) (2.91 kg)

Offer Sustainability

Sustainable offer status Green Premium product

REACH Regulation [REACH Declaration](#)

EU RoHS Directive Compliant
[EU RoHS Declaration](#)

Lead free Yes

Mercury free Yes

RoHS exemption information [Yes](#)

Optimized Energy Efficiency Energy efficient product

Take-back Take-back program available

Contractual warranty

Warranty 2 years repair or replace

Recommended replacement(s)