



samlexamerica®

# 80A

## Rackmount Switching Power Supplies

Model  
SEC-80BRM  
80 Amps



## 2 YEAR LIMITED WARRANTY

### Design Features

- Voltage/Ampere meter
- Module status LEDs, fault indicator LEDs and fault alarm are standard features on all models
- Highly regulated output voltage
- Short circuit protection and overload current
- 25 pin D-sub connector for remote monitoring system

<b>MODEL NO.</b>	<b>SEC-80BRM</b>
<b>NUMBER OF MODULES</b>	4
<b>INPUT VOLTAGE RANGE</b>	105 to 125 VAC, 50 / 60 Hz
<b>INPUT CURRENT</b>	16 A
<b>NOMINAL OUTPUT VOLTAGE</b>	13.8 VDC
<b>NO LOAD OUTPUT VOLTAGE</b>	14 VDC
<b>FULL LOAD OUTPUT VOLTAGE</b>	13.45 VDC
<b>OUTPUT REGULATION</b>	1%
<b>CONTINUOUS OUTPUT CURRENT</b>	80 A
<b>SURGE OUTPUT CURRENT</b>	92 A
<b>OUTPUT CURRENT LIMIT</b>	96 A
<b>MAXIMUM BATTERY CHARGING CURRENT</b>	8 A
<b>OUTPUT RIPPLE (PEAK TO PEAK)</b>	150 mV
<b>OUTPUT NOISE (PEAK TO PEAK)</b>	0.8 V
<b>COOLING</b>	Forced air, 2 fans
<b>PROTECTIONS</b>	Short circuit, current limit, fan failure (LED and buzzer), input surge suppression
<b>OPERATING TEMPERATURE</b>	0 - 40° C
<b>POWER CORD</b>	12 AWG / 3 conductor
<b>POWER CORD PLUG</b>	125 V, 20 A, NEMA 5-20P
<b>MODULE FUSE</b>	250 V, 4 A
<b>UNIT CIRCUIT BREAKER</b>	125 / 250 V, 25 A
<b>DIMENSIONS (19" Rack Mount, 2U height), MM (L x W x H)</b>	483 x 404 x 91.4
<b>DIMENSIONS (19" Rack Mount, 2U height), INCHES (L x W x H)</b>	19 x 15.9 x 3.6
<b>WEIGHT, KG</b>	10.7
<b>WEIGHT, LB</b>	23.5

NOTE: Specifications are subject to change without notice

12001-SEC-80BRM-0319