



EM-M11001-FME-195 NMO 3/4" Hole Mount Cable Assembly

- 17 ft. LL195 w/FME Connector attached
- Low-Profile
- Easy installation: Designed for a one-operator installation from above surface
- All brass components with silver plated contact.
- Heavy Duty mounting claw for reliable contact and ground connections

Electrical Specifications

Radio Termination Adapters



EMFME-MP

FME Male to Mini UHF



EMFME-PL

FME Male to PL259 Plug



EMFME-QP

FME Male to QMA Plug



EMFME-TP

FME Male to TNC Plug



EMFME-NP

FME Male to N Male Plug

Frequency Band	30 – 1000 MHz
VSWR ¹	1.5:1 typical
Impedance	50Ω
Cable Insertion Loss	2.5 dB, max
Power Rating ²	100 W @1000 MHz

Mechanical Specifications

Mounting Height	0.375 in. (9.5 mm)
Mounting Hole	0.75 in. (19.05 mm)
Outside Mounting Diameter	1.13 in. (28.7 mm)
Mounting Application / Type	Thru-hole
Cable ³	Low Loss 195
Cable Length	17 ft. (5.1 m)
Connector Type	FME Connector Attached
Mounting Material	Brass
Operating Temperature Range	-40° to 85° C
Mounting Surface Weather Seal	O-Ring
Corrosion	Salt Fog
Humidity	95% RH

1. Antenna / Frequency-Dependent 2. VSWR, Temperature and Altitude Dependent

3. Other cable types available upon request

Specifications subject to change without notification

ELECTRO-MAGWAVE, INC.

10221 Sweet Valley Drive, STE 1 Valley View, OH 44125 † 216-453-1160 † 216-447-8828 www.emwaveinc.com