


Intermod Supression Panels 700-1000 MHz IM Suppression Pannels **PC4** Series

PC4213 I.M. Suppression panel, rack mount, dual stage isolator, 30+60 Watt loads, 806-960 MHz

- Dual stage isolator with 30+60 Watt loads provides 75 dB (typ) isolation
- · Can be tuned over the 806-960 MHz band and comes with built-in harmonic filters
- · Compact design shipped precisely tuned to customer specified frequency

Sinclair's PC series panels incorporate high performance single- or dual-stage isolators with various load terminations and Sinclair-built harmonic filters. These compact units offer optimum intermodulation control in a 19-inch rack mounted configuration. They are shipped precisely tuned to customer specified frequency, and exhibit 25 dB or 50 dB isolation when equipped with single- or dual-stage isolators respectively. Various load configurations are available depending on system power level and VSWR protection required.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com



Intermod Supression Panels 700-1000 MHz IM Suppression Pannels **PC4 Series**

A Norsat Company Norsat

Frequency Range	MHz	806 to 960
Bandwidth	MHz	25
VSWR (max)		1.25:1
Isolation (typ)	dB	75
Average Power Input (max)	W	125
Connectors		N-Female
Insertion Loss (typ) Tx to Ant	dB	0.6
Insertion Loss (max) Tx to Ant	dB	0.9
Isolation (min)	dB	50
Width	in (mm)	19 (483)
Width Depth	in (mm)	9.13 (232)
Mechanical Specifications Width Depth Length/ Height Shipping dimensions	,	, ,
Width Depth Length/ Height Shipping dimensions	in (mm) in (mm)	9.13 (232) 1.75 (44)
Width Depth Length/ Height	in (mm) in (mm)	9.13 (232) 1.75 (44)

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		DC/1213	leeue: 6	Dated: 24-09-15