



NMO MAGNETIC MOUNTS

Vehicle Mobile Radio Mounts

FEATURES AND BENEFITS

- Corrosion resistant materials used throughout for high durability and weather resistance
- Neoprene seal for moisture protection
- High 80-lb pull strength will allow antenna to stay put
- Optional rubber boot provides additional protection to mounting surface
- Triple reinforced coax strain relief eliminates cable pull out
- 3-1/4" diameter

3/4" STYLE MAGNETIC MOUNTS *

MODEL	CONNECTOR TYPE
Chrome Models with 12' of RG58A/U Stranded Center Cable	
G8-L	No connector
G8BI	BNC crimp, installed
G8MI	Minu UHF crimp, installed
G8N	N crimp
G8PI	UHF (PL259) crimp, installed
GR8PI	UHF (PL259) crimp, installed
G9PST	UHF (PL259) Teflon® solder
Chrome Models with 12' of RG58U Solid Center Conductor Cable	
G8U	No connector
G8UM	Minu UHF crimp
G8UT	TNC crimp

MODEL	CONNECTOR TYPE
Chrome Models with 12' of RG8X Low Loss Cable	
G8XN	N crimp, installed
G8XNI	N crimp, installed
G8XTI	N crimp, installed
GR8PI	Rubber boot option - RG58A/U w/ PL259 installed
Black Models with 12' of RG58A/U Stranded Center Cable	
GB8	RG58U
GB8U	RG58U
GB8USM	RG58U
GB8UM-L	RG58U
GBR8PI	Rubber boot option - RG58A/U w/ PL259 installed
Chrome Model with 17' ATX195 Cable	
GNNMI518	N-male crimp, installed

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE, TE Connectivity, TE connectivity (logo), and EVERY CONNECTION COUNTS are trademarks owned or licensed by the TE Connectivity plc family of companies. Other product names, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, complete, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event will TE be liable for any direct, indirect, incidental, special or consequential damages arising from or related to recipient's use of the information. It is the sole responsibility of recipient of this information to verify the results of this information using their engineering and product environment. Recipient assumes any and all risks associated with the use of the information. Antenna performance may vary. TE is a component manufacturer, and customer and/or end-user is responsible for all end-use compliance and regulatory requirements.

©2025 TE Connectivity. All Rights Reserved.

05/25 Original