



FG8243

Omnidirectional Fiberglass Base Station Antenna 824-896 MHz

TE Connectivity's FG8243 omnidirectional fiberglass base station antennas are collinear designs enclosed in a high-density fiberglass which is covered with a protective ultraviolet inhibiting coating. The radiating elements are made from high-efficiency copper and are carefully phased to provide maximum gain in the horizontal plane. The mounting sleeves are tuned to eliminate RF currents from the transmission line, resulting in a cold sleeve allowing great freedom in mounting. This high quality and well- focused beam provides the highest gain and best efficiency.

FEATURES

- Highly stable PC board matching section
- Superior quality design
- Highest gain and best matching efficiency in the industry
- Special UV treated radome/resists sun damage
- N-female industry standard connector
- 100% tested on a Network Analyzer

ELECTRICAL SPECIFICATIONS

Operating Frequency (MHz)	824-896
VSWR	<2:1
Gain (dBi)	4.5
Nominal Impedance (Ohms)	50
Max Power - Ambient 25°C (W)	100
Polarization	Vertical
Vertical Plane 3 dB Beamwidth (°)	60
Horizontal Plane 3 dB Beamwidth (°)	360

MECHANICAL SPECIFICATION

Dimensions - diameter x height - mm (inches)	33.3 x 588.7 (1.31 x 23.125)
Weight - kg (lbs.)	24 (1.5)
Cable Type	None
Radome Material	UV-Treated Fiberglass
Lightning Protection	Lightning Arrestor LABH350NN (sold separately)
Connector Type	N-Female Connector

MECHANICAL SPECIFICATION

Operating Temperature - °C (°F)	-30 to +70°C (-22 to +158°F)
Storage Temperature - °C (°F)	-30 to +70°C (-22 to +158°F)
Rated Wind Velocity - km/hr (mph)	210 (125)
Rated Wind Velocity (with .5" radial ice) - km/hr (mph)	137 (85)
Lateral Thrust @ 125 mph Wind Velocity - kg (lbs.)	26 (57)
Wind Resistance - cm2 (ft2)	200.67 (0.216)
Material Substance Compliance	RoHS Compliant

ACCESSORIES




Lightning Arrestor
LABH350NN
(Sold Separately)




FM2 Mounting Kit
(Sold separately)

RADIATION PATTERNS



Azimuth Pattern



Elevation Pattern

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE, TE Connectivity, TE connectivity (logo), and EVERY CONNECTION COUNTS are trademarks owned or licensed by the TE Connectivity plc family of companies. Other product names, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, complete, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event will TE be liable for any direct, indirect, incidental, special or consequential damages arising from or related to recipient's use of the information. It is the sole responsibility of recipient of this information to verify the results of this information using their engineering and product environment. Recipient assumes any and all risks associated with the use of the information. Antenna performance may vary. TE is a component manufacturer, and customer and/or end-user is responsible for all end-use compliance and regulatory requirements.

©2025 TE Connectivity. All Rights Reserved.

05/25 Original