

## Wideband RF Isolator

### Electrical Specifications

Frequency Band	650-1000 MHz
Bandwidth	Single Frequency
Input Power (Max.)	150 W
Reflected Power (Max.)	75 W
Isolation Ant-Tx (Min. / Typ.)	65 / 75 dB
Isolator Stage	Dual
Load Termination	30/75 W
Insertion Loss (Max.)	0.60 dB
Return Loss (Min.)	28+ dB
Impedance (Nom.)	50 $\Omega$
RF Connectors	N Female

### Mechanical Specifications

Finish	Nickel
Overall Size (HxWxD)	1.5" x 6" x 7.6" (38 x 152 x 193 mm)
Net Weight	3 lbs (1.4 kg)
Ship Weight	5 lbs (2.3 kg)

### Environmental Specifications

Operating Temp. Range	14 to 140 °F (-10 to +60 °C)
-----------------------	------------------------------



EMR Corp W-Series (Wideband) line of ferrite Isolators/Circulators have excellent narrow band as well as broadband specifications. These isolators maintain low insertion loss with stable operation while providing excellent isolation at 30+ dB for single and 65+ dB for dual units. Wider bandwidths help to facilitate stocking requiring fewer SKU Nos for inventory making the W-Series an ideal choice for distributors.

### Product Features

- Available from 30 MHz to 1.3 GHz Bands
- Wider Bandwidths available with changes to specifications.

